

Mercury Dual-band Wireless WiFi Repeater 1200M Model: MAC1200RE



Overview:

Speed Spread Signal

Wi-Fi Signal coverage is narrow, a route not enough? This product is provided with high-speed expansion of Wi-Fi signals. Bedroom cinema, brush microblogging living room, sun terrace self-timer, all easy to get.

Four External Antennas, Strong Expansion

Extended wireless rates of up to 1200M; 2.4G 300Mbps, 5.0GHz 867Mbps. Four external antennas, the signal is stronger with farther coverage.

Quick Setup, Plug and Play

Using intimate wall plug design, using a mobile phone or Pad can simply complete the initial setup. With a powerful memory, once setup is complete, according to actual needs in the socket where there is plug and play.

Intelligent Lights, At a Glance

It comes with an indicator light, by clear and intuitive color changes to help you find the right placement of the expander, to achieve a better Wi-Fi expansion effect.

Features:

- 1. Comply with IEEE 802.11ac, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b, IEEE 802.11a standards.
- 2. Wireless transmission rate up to 1167Mbps.
- 3. Wall-mounted design, once set, transfer anywhere.
- 4. Easy to set up the page, easy to complete wireless expansion in three steps.
- 5. MIMO technology and CCA technology to improve wireless stability and expand wireless coverage.
- 6. The orange indicator light indicates that the placement position is too far, and the green indicator light indicates that the placement position is the best.
- 7. Built-in DHCP server can automatically and dynamically assign IP addresses.
- 8. Support WPA/WPA-PSK, WPA2/WPA2-PSK security mechanism.

Specifications:

Standard	IEEE 802.11ac, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b, IEEE 802.11a
Button	Reset key *1
LED	SYS *1
Wireless Speed	11N: 300Mbps
	11AC: 867Mbps
Frequency Range	2.4 GHz + 5GHz
Wireless Security	Supports WPA-PSK / WPA2-PSK
Antennas	4 External Omni Directional antennas
Power Supply	Input 100-240V ~ 50/60Hz
Environment	Operating temperature: $0^{\circ}C \sim 40^{\circ}C$
	Storage temperature: $-40^{\circ}C \sim 70^{\circ}C$
	Operating humidity: 10%~90% non-condensing
	Storage humidity: 5%~90% non-condensing
Dimensions	112mm × 70mm × 39mm (L × W × H)

Setup Guide:

Step1: Plug in power. After connecting WiFi of this device, open browser on smart phone, then type into tplogin.cn to setup admin password. After this, click log in (Next).

Step2: This device searches nearby 2.46 WiFi network. After finish scanning, select the WiFi that will be extended.

Step3: Type the password of host WiFi [which will be extended] and setup the new SSID of WiFi Extender, then click the "next". Advice: new SSID may be same with host WiFi.

LED status:

- The LED is red and blinking, shows it is extending WiFi.
- The LED is solid green or yellow, shows it works successfully.
- The LED is solid red, shows it works unsuccessfully.



