

# WECON 3.5" Human Machine Interface

## Model:LEVI350T



### Features:

- ◇Hardware: ARM9 2416 CPU 400MHz RISC
- ◇Display size: 3.5 inch
- ◇Resolution: 320\*240 TFT LCD 65,536 colors
- ◇Interface: Support RS232/RS485/RS422
- ◇Storage: 128M FLASH, 64M DDRAM II

### Specifications:

#### Hardware

OS	2416 Platform
CPU	32-bits 400MHz RISC
Touch Screen	High precision four-wire resistive

#### Display

Screen Size	3.5 inch
Resolution	320*240
Brightness	300 nit
Contract	500:1
Backlight	LED
Backlight Life	50,000 hours
Colors	65536 colors (16bit)

#### Storage

Flash	128MB
RAM	64M DDRAM
RTC	256KB
SD card	Yes

#### Ports

USB Port	USB Host USB 2.0 x 1 USB Client USB 2.0 x 1
----------	---

<b>Printer Port</b>	Serial port Printer
<b>Serial Port COM1</b>	RS232/RS422/RS485/(RS232+RS485)
<b>Serial Port COM2</b>	No
<b>Serial Port COM3</b>	No
<b>Ethernet</b>	No
<b>CAN</b>	No

#### Power

<b>Allowed Power Fail</b>	<5ms
<b>Power Supply</b>	24V DC(12~28V DC)
<b>Power</b>	<5W
<b>Power Isolation</b>	Built-in Power Isolation
<b>Withstand Voltage</b>	500V AC (<1 minute)
<b>Insulation Resistance</b>	Upon 20M $\Omega$ 500VDC
<b>Seismic resistance</b>	10 ~ 25 Hz (X, Y, Z direction 2G/30 minutes)

#### Environment

<b>Cooling</b>	Air cooling
<b>Protection</b>	IP65 (Front panel)
<b>Storage Temperature</b>	-20 ~ 70°C
<b>Environment.Working Temperature</b>	-10°C ~ 60°C
<b>Humidity</b>	10 ~ 90%RH

#### Specification

<b>Enclosure</b>	ABS
<b>Dimension(mm)</b>	96.0W*81.0H*33.0D
<b>Mounting size(mm)</b>	91.0W* 73.0H



#### Certification



<b>CE Certification</b>	EN61000-6-2:2005, EN61000-6- 4:2007 Standard
<b>FCC Certification</b>	FCC Class A

#### Software

<b>Software</b>	LeviStudioU Programming Software
-----------------	----------------------------------

#### HMI Dimensions:





#### Screen Size:

430: 4.3"  
700: 7"  
102: 10.2"  
910: 10.4"

#### Type :

E: Standard  
T: Standard  
EL: Simplified

## LEVI700E-N

Generation: LEVI

#### Expansion:

N: Ethernet  
C: CANBus  
E: Third serial port  
TTS: Text to speech  
V: analog video





#### Serial Printer:

Print out the selected content in the scope of Printer Objects. The printer parts only print out the content which can be displayed by screen printer



#### Multi-Link:

HMI's Interconnection Mode allows user connecting more than one Wecon HMI (up to 255 ) to external device, communication speed is much faster than Modbus protocol.



#### Recipe:

Restore the data to certain register from USB flash disk, SD Card or HMI local flash, used for backup as well, the format of recipe is compatible with CSV opening by OFFICE Excel.



#### SMS:

Set receiver and sender for the SMS module, short message will send to receiver when alarm, also controller will be activated by the short message containing certain operator from mobile phone.



#### Installment:


When HMI system time surpasses the installment setting time, installment password input dialog will pop up. Only after entering the right password, the HMI can continue to work.



User restriction:

Users are authorized to change the way of HMI behaves.

Product Photos:



*Made in China*