

PNEUMATIC MUFFLER 3/8"

MODEL: PSL-03 3/8 Black



Description:

The plastic silencer is designed to give excellent noise reduction with a minimum effect on air efficiency. The "Trimline" design allows for locating the silencer in the tightest places without extra plumbing or fittings. Fits directly into the exhaust port of most commercial valves. Open surface area of element allows for rapid discharge of air without undesirable back pressure. Polyethylene element. Sound pressure level 67dBA at 20 PSIG inlet and 84dBA at 100 PSIG inlet.

Features:

- Compact, lightweight
- Easy to install
- Excellent noise reduction
- Protects components from contamination
- Color: black

Specifications:

- Maximum pressure: 150 pounds per square inch
- Lower Temperature Rating: 14 degrees Fahrenheit
- Upper Temperature Rating: 140 degrees Fahrenheit
- Pressure Flow rating: 124 cubic feet per minute

Dimensions:

model	Inch Thread	Thread Φ D	A	B	Φ C	H2	Weight
PSL-01	1/8"	9.5mm	6.6	37	14.5	8.1	3g
PSL-02	1/4"	12.5mm	10.1	65	20.8	17.5	11g
PSL-03	3/8"	16mm	12.8	84.5	24.3	20.5	19g
PSL-04	1/2"	19.5mm	13.5	93.5	29.7	25.1	28g



Made in China