

PNEUMATIC MUFFLER 1/4"

MODEL: PSL-02 1/4 Blue



Description:

The plastic silencer is designed to give excellent noise reduction with a minimum effect on air efficiency. The "Trimline" design allows for locating the silencer in the tightest places without extra plumbing or fittings. Fits directly into the exhaust port of most commercial valves. Open surface area of element allows for rapid discharge of air without undesirable back pressure. Polyethylene element. Sound pressure level 67dBA at 20 PSIG inlet and 84dBA at 100 PSIG inlet.

Features:

- Compact, lightweight
- Easy to install
- Excellent noise reduction
- Protects components from contamination
- Color: blue

Specifications:

- Maximum pressure: 150 pounds per square inch
- Lower Temperature Rating: 14 degrees Fahrenheit
- Upper Temperature Rating: 140 degrees Fahrenheit
- Pressure Flow rating: 124 cubic feet per minute

Dimensions:

model	Inch Thread	Thread ΦD	A	B	ΦC
PSL-01	1/8"	9.5mm	6.6	37	14.5
PSL-02	1/4"	11mm	10	40	15
PSL-03	3/8"	16mm	12.8	84.5	24.3
PSL-04	1/2"	19.5mm	13.5	93.5	29.7



Made in China