# VeraPlus



## Advanced Home Controller













### Overview

- Compatible with Z-Wave Plus, Wi-Fi, ZigBee, and Bluetooth products
- Supports over 200 devices in one home or business automation system
- Wi-Fi compatible with 802.11 a/b/g/n/ac
- Memory: DDR3 256MB
- Provides Open WRT SDK for Development

- Available for US and EU markets; other international markets available upon request.
- No monthly fees; no annual contracts.
- Works with 1700+ devices including thermostats, motion sensors, smoke detectors, security devices, IP cameras, door locks, and energy devices, plus many more.

### Additional Views & Dimensions



# VeraPlus



## Advanced Home Controller

#### Network

#### Ethernet

WAN: (10/100/1000 Mbps)

#### Wireless

Wi-Fi: IEEE 802.11 b/g/n and 802.11 a/n/ac

ZigBee: Built-in ZigBee on Board

Z-Wave: Built-in Z-Wave Module on Board

Bluetooth LE: Built-in Bluetooth LE Module on Board

#### Software

#### **Applications**

Vera UI 7 or higher

#### Hardware

**Processor and Memory Processor:** 880MHz MIPS SoC, Dual-Core

NAND Flash: 128MB **DDR3:** 256MB

#### Power Adapter

Input: 100-240VAC, 50-60Hz Output: 12VDC, 1.5A, Max. 12Watts

#### Connectors

- 1 DC Power Jack
- 1 RJ-45 Connector
- 1 External USB Connector

#### **Antennas**

- 4 Wi-Fi Internal Antennas (combine 1 Bluetooth LE Internal Antenna)
- TigBee Internal Antenna
- 1 Z-Wave Internal Antenna

#### **LEDs and Buttons**

- 4 LEDs: Single-Color LED (Green)
- 3 Buttons: Reset, RF Select, RF Sync

#### Dimensions $(H \times W \times D)$

 $1.3 \times 7.7 \times 5.0$  in  $(34 \times 196 \times 127$  mm)

#### Compliance

FCC, CE, RoHS

#### Weight

1.4 lbs

#### Environment

#### Operation

Temperature: 0° - 40°C (32° - 104°F) **Humidity:** 10% - 80% RH (non-condensing)

Temperature: -20° - 60°C (-4° - 140°F) Humidity: 0% - 90% RH (non-condensing)

#### Accessories

#### Accessories

Power Adapter: 12VDC, 1.5A, Max 12W

Made in Taiwan