

# Twinkler Handheld Satellite Finder

Model:SF-620S



## Features:

- 1080P, FULL HD,DVB-S/S2 Satellite Multi-functional Handheld HD Satellite Finder
- 4.3 inch TFT LCD Display
- Watch live FTA program in full color
- 13V/18V/22K/Lock/Power status display
- LNB short-circuit alarm and protection function
- DiSEqC / USALS 1.0 / 1.1 / 1.2 / USALS
- PVR, Timeshift and Multi-media Play Supported
- Multi-lingual OSD for world use
- USB2.0 interface available for software update, content recording
- LED torch and double-speaker inside
- Spectrum Analyzer
- Network Extension: CS, YouTube, IPTV...
- CCTV Camera tester in CVBS
- Support USB WiFi

## Technical Parameters:

| DVB-S/S2 Measurement |   |
|----------------------|---|
| Connector            | Male type, with one double negative connector |
| Modulation Type      | QPSK, 8PSK, 16APSK, 32APSK                    |
| Symbol Rate          | 1Mbps ~ 60Mbps                                |
| Frequency Range      | 950MHz ~ 2150MHz                              |
| Input Signal Level   | -65dBm ~ -25dBm                               |

| Video/Audio Decoder |                    |
|---------------------|--------------------|
| Video               | MPEG 2&4           |
| Data Rate           | Up To 15M bits/s   |
| Resolution          | 720*576, 720*480   |
| Video Format        | PAL / NTSC / SECAM |

|                |                         |
|----------------|-------------------------|
| Audio          | MPEG 1 layer 1&2&4      |
| Type           | Stereo                  |
| Sampling Rates | 32KHz 44.1KHz and 48KHz |

| <b>Interface</b>               |     |
|--------------------------------|-----|
| RF Input                       | Yes |
| AV output                      | Yes |
| AV input                       | Yes |
| Mini USB interface- 12V output | Yes |
| HDMI 1.4                       | Yes |
| USB2.0                         | Yes |
| DC interface                   | Yes |

| <b>General</b>        |  |
|-----------------------|--|
| Operating Temperature | 0°C ~ +50°C                            |
| AC/DC Adapter         | AC 110V/60Hz/220V/50Hz±10% DC 12V/1.5A |
| Li-ion Battery        | 5000mAh                                |
| Charge Time           | Less than 4 hours                      |
| Working Time          | Around 3-4 Hours (Fully charge)        |
| Weight                | 0.58KG                                 |
| Dimensions (LxWxH)    | 200mm*120mm*60mm                       |

*Made in China*