

Frequency Meter Model: FC-1200



Features:

- Hand-held and pocket size
- Wide measuring range up to 1.25GHz
- Good resolution, 0.1Hz min display unit for 10MHZ range
- Auto power off and manual power off
- LCD display for low power consumption and clear read-out even in bright ambient light condition
- Low PPM crystal time base to offer high accuracy measurement

Specifications:

Display	13mm (0.5") LCD 8 dgts
Measurement	Freq, data hold, relative, memory, period
Frequency range	Channel A: 500MHz-1250MHZ Channel B: 10Hz-10MHz
Period range	10Hz-10MHz
Frequency accuracy	$\pm(1\text{PPM}+1\text{dgt})$, 23 \pm 5°C
Time base circuit	4.194 MHz quartz crystal
Time base temp coeff.	0.1PPM/per °C
Over-input	1250MHz&500MHz range: max 5 Vp-p
Input connector	BNC female
Case	Durable & strong ABS, plastic housing
Operating temp.	0°C~50°C
Operating humidity	max 90%R.H.
Power supply	4x1.5V, AA size
Power consumption	1250MHz&500MHz range: DC 100mA 10MHz&period range: DC 45mA
Dimensions	173x80x35 mm
Weight	340g



LUTRON ELECTRONIC

The Art of Measurement

Made in Taiwan