


C125 Series

Dip IC Socket, 2.54mm(0.100")



Ordering Information




C125 - 6 40 - 1

Series No. Deviation:
Row Spacing: 1 or 2,
 Only for 24 & 28 Pos.
 No. of Pins:
 06,08,14,16,18,
 20,24,28,32,40,42

Specifications:

Contact Resistance: 30mΩ @ 100mA DC
Insulator Resistance: 1000MΩmin. @ 500V DC
Current Rating: 1AMP
Voltage: 500V AC For 1 minute
Operating Temperature: -55°C~+105°C
Contact: Brass or Phosphor Bronze, Stamped
Housing: PBT, UL94V-0

Pos.	A	B	C	D	Pos.	A	B	C	D
06	7.62	5.08	10.16	7.62	24-2	30.48	27.94	17.78	15.24
08	10.16	7.62	10.16	7.62	28-1	35.56	33.02	10.16	7.62
14	17.78	15.24	10.16	7.62	28-2	35.56	33.02	17.78	15.24
16	20.32	17.78	10.16	7.62	32	40.54	38.10	17.78	15.24
18	22.86	20.32	10.16	7.62	40	50.80	48.26	17.78	15.24
20	25.40	22.86	10.16	7.62	42	53.21	50.80	17.78	15.24
24-1	30.48	27.94	10.16	7.62					



Made in China