

VOLTAGE/CURRENT CALIBRATOR

Model : CC-421

ISO-9001, CE, IEC1010



LUTRON ELECTRONIC

VOLTAGE/CURRENT CALIBRATOR

Model : CC-421

FEATURES

* The instruments Powers or Measure a two-wire current loop. Four function provide the quality and accuracy of handheld calibrator : a. Precision current source. b. Measurement of a current signal. c. Power and measurement of two wire loop. d. Precision DC mV source.	* Portable instrument for calibrating process devices and measuring process signals. * Adjustable 0-24 mA current source. * Adjustable -199.9 mV to +1.99.9 mV DC voltage source. * Current calibrator drives loads up to 500 ohms.
-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

GENERAL SPECIFICATIONS

Display	LCD display, max. display counts 1999. 13 mm (0.5") digit size.	Operating Temperature & Humidity	0°C to 50°C (32°F to 122°F). Less than 80% RH.
Function	1) Current source 2) Current measurement 3) Power and current measurement of two wire loop 4) DC mV source	Power Supply	006P DC 9V, MN1604/PP3 battery or equivalent. Alkaline type or heavy duty type.
		Dimension	185 x 78 x 38 mm (7.3 x 3.0 x 1.5 inch).
		Weight	265 g/0.58 LB (including battery).
Sampling Time	Approx. 0.4 second.	Accessories Included	Operational manual..... 1 PC. Cable with the alligator pairs (red & black), LN-TL421..... 1 PC.

ELECTRICAL SPECIFICATION (23 ± 5 °C)

Current source			Current measurement		
Range	Display Resolution	Accuracy	Range	Display Resolution	Accuracy
0 - 19.99 mA	0.01 mA	± (0.25 % FS + 1 d)	0 - 19.99 mA	0.01 mA	± (0.25 % FS + 1 d)
0 - 24 mA	0.1 mA	± (0.5 % FS + 1 d)	0 - 24 mA	0.1 mA	± (0.5 % FS + 1 d)
Power and current measurement of two wire loop			DC mV source		
Range	Display Resolution	Accuracy	Range	Display Resolution	Accuracy
0 - 19.99 mA	0.01 mA	± (0.25 % FS + 1 d)	- 199.9 mV to + 199.9 mV	0.1 mV	± (0.25 % FS + 1 d)
0 - 24 mA	0.1 mA	± (0.5 % FS + 1 d)			
* Provides power DC 12V 2 V to the loop and measures current.			* Output measured load impedance should > 1 K ohms.		
* FS : full scale			* FS : full scale		

* Appearance and specifications listed in this brochure are subject to change without notice.

0408-CC421

Made in Taiwan