

Aluminum Foil Waterproof Tape



Description:

Aluminum Foil Tape, Butyl Waterproof Tape Leak Proof, Super Fix Repair Wall Crack Easy to use.

Features:

- Resistant to chemicals, heat and weather.
- High viscosity cold weather adhesive.
- These tapes have butyl rubber, a high-tack and pressure-sensitive sealant with tack.
- It has excellent adhesion even at low temperatures.
- Block moisture and odors. They can form an instant seal, prevent water, air or dust from entering, and remain permanently soft.
- Excellent insulation properties.
- Water resistant and UV resistant.

Specifications:

- Material: aluminum foil + butyl
- Width: 5cm
- Length: 5m

Applications:

This tape is specially used for occasions that require moisture resistance and chemical resistance, thermal conductivity, flame retardancy, heat and light reflectivity.

How to Use:

- 1- Before construction, make sure the surface is clean and dry.
- 2- Peel off the released film and apply RV roof sealing tape.
- 3- Press the butyl sealant repeatedly until the tape is completely stuck to the surface.
- 4- Tools needed (not included in the package): cleaning tools, scissors, trimming tools, gloves.

Note:

- Ensure that the construction surface is dry.
- There should be no impurities on the construction surface, otherwise it will affect the viscosity of the tape.
- The tape is too narrow to affect the waterproof effect.
- Cannot be used on the back of water, it will fall off.
- The roof waterproof finds the leak point and does not work.
- Due to the strong stickiness, please wear gloves to prevent your hands from sticking.
- In winter, it is best to use a hair dryer to heat the camper's roof before installation.
- After applying it within 24 hours, do not peel it off.
- Do not use with benzene, vinyl, silicone and other waterproof materials.