

SMPS 5V 50A



Specifications:

Input	Commercial Grade	AC220±20%±25%V, AC110±20%±25%V Frequency: 47~63Hz
	Industrial Grade	AC220±25%±40%V, AC110±25%±40%V Frequency: 47~63Hz
	Inrush current	cold start, 30A/230V
Output	Output Voltage Precision	Commercial:±1% max Industrial:±0.5% max
	Linear regulation	Commercial: ±0.5% max Industrial:±0.3% max
	Temperature Coefficient	Commercial:0.03%/ Industrial:0.02%/
	Output voltage adjustment range: ±10% Ripple & Noise (mVPP)<1% output voltage Efficiency≥75%	
	Protection	Overload: 105%~150%Rated power, self-recovery. Over voltage: 115%~135% VoltageV1.
Insulating Strength	I/P -O/P: 1.5KVAC/1min, 5Ma I/P -F/G: 1.5KVAC/1min, 5Ma O/P-F/G: 0.5KVAC/1min, 5Ma Leakage current <0.5mA/ 230VAC	
Insulating Resistance	I/P -O/P, I/P -F/G, O/P-F/G≥50MΩ, DC500V.	
Working Temperature	Commercial: 0~45,20%~90%RH (non condensing)	
	Industrial: -25~55,20%~90%RH (non condensing)	
Storage Temperature	Commercial: -20~65,10%~95%RH (non condensing)	
	Industrial: -30~85,10%~95%RH(non condensing) Altitude< 2,000m	
Cooling Way	Natural air cooling	
Remark	Various dimensions and other output can be ordered according to your requirements.	

Made in China