

LCD Projector Promethean

Model: PRM-30A



Features:

- LCD projector
- 2500 ANSI lumens
- WXGA (1280 x 800)
- Widescreen
- High Definition 720p

Specifications:

Display:

- Display Resolution Abbreviation: WXGA
- Projector Image Brightness: 2500 lumens
- Type: LCD projector
- Input Device Form Factor: External

Interface Provided:

Interface (Output): HDMI

- Qty: 1
- Connector Type: RJ-45
- Interface (Output): Network
- Connector Type: 15 pin HD D-Sub (HD-15)
- Interface (Output): VGA input
- Connector Type: Mini-phone stereo 3.5 mm
- Interface (Output): Audio line-in
- Connector Qty: X 2
- Connector Type: RCA

Interface (Output): Composite video input

- Connector Type: 4 pin mini-DIN
- Interface (Output): S-video input
- Connector Type: 9 pin D-Sub (DB-9)
- Interface (Output): Serial RS-232
- Purpose Location: Management

Interface (Output): VGA

- Cable Connectivity Details Type: VGA cable
- Display (Projector) Image Contrast Ratio: 500:1
- Max Resolution: 1280 x 800

Software Type:

- Drivers & Utilities

Environmental Parameters:

- Max Operating Temperature: 95 °F
- Min Operating Temperature: 41°F
- Sound Emission: 36 dBA
- Sound Emission (Economic Mode): 29 dBA

Power Device:

- Form Factor: Internal
- Frequency Required: 50/60 Hz
- Nominal Voltage: AC 120/230 V
- Power Consumption Operational: 317 Watt
- Power Consumption Stand by Sleep: 0.8 Watt
- Type: Power supply

Video Input:

- Analog Video Format: NTSC 3.58 , NTSC 4.43 , PAL-B/G , PAL-D , PAL-H , PAL-I , PAL-M , PAL-N , SECAM B/G , SECAM D/K , SECAM K1, SECAM L
- Analog Video Signal: Composite video, RGB, S-Video
- Digital Video Standard: High-Definition Multimedia Interface (HDMI)
- Video Interfaces: Composite video, HDMI, S-Video, VGA
- Video Modes: 1035i, 1080i, 480i, 480p, 575i, 576i, 720p

Video Output:

- Analog Video Signal: RGB

Projector:

- Brightness: 2500 lumens
- Brightness (Reduced): 1900 lumens
- Class: Digital projector
- Color Support: 16.8 million colors
- Controls & Adjustments: Keystone correction

Display Resolution:

- Abbreviation: WXGA
- HD Image Format: 720p
- High Definition: High Definition
- Image Contrast Ratio: 500:1
- Max H-Sync Rate: 90 kHz
- Max Image Size: 110 in
- Max Resolution (Resized): 1680 x 1050
- Max Screen Distance: 4 ft.
- Max V-Sync Rate: 85 Hz
- Min Image Size: 50 in
- Min Screen Distance: 1.8 ft.
- Native Aspect Ratio: Widescreen
- Native Resolution: 1280 x 800
- OSD Languages: Arabic , Brazilian Portuguese , Chinese (simplified) , Chinese (traditional) , Danish , Dutch, English, Finnish, French , German , Hungarian , Italian , Japanese , Kazakh , Korean , Norwegian , Polish, Portuguese, Romanian, Russian, Spanish, Swedish , Turkish
- Portability: Non-portable
- Projector Features: 16:10 aspect ratio support, 16:9 aspect ratio supports, 4:3 aspect ratio supports, Closed Caption, Direct Power Off , Direct Power On
- Recommended Use: Presentation and multimedia
- Type: LCD projector

Projector Lamp:

- Lamp Capacity: 230 Watt
- Lamp Life Cycle: 3000 hour(s)
- Lamp Life Cycle (Economic Mode): 4000 hour(s)

Projector Lens System:

- Focus Type: Manual
- Keystone Correction Direction: Vertical
- Vertical Keystone Correction: -20 / +20

Miscellaneous:

- Color: Silver
- Included Accessories: Cable cover, Wireless remote control
- Security Features: Pin code, Security lock slot (cable lock sold separately)

Package Include:

- Contents- Remote
- Manual
- Power cords
- VGA cable