



■ Features :

- 2:1 wide input range
- Protections: Short circuit / Overload / Over voltage / Over temperature
- Built-in EMI filter, low ripple noise
- 100% full load burn-in test
- Fix switching frequency at 67KHz
- Low cost
- High reliability
- 2 years warranty


SPECIFICATION



MODEL		PSD-05-05
OUTPUT	DC VOLTAGE	5V
	RATED CURRENT	1A
	CURRENT RANGE	0 ~ 1A
	RATED POWER	5W
	RIPPLE & NOISE (max.) Note.2	50mVp-p
	VOLTAGE TOLERANCE Note.3	±2.0%
	LINE REGULATION	±1.0%
	LOAD REGULATION	±1.0%
	SETUP, RISE, HOLD UP TIME	1.2s, 20ms, --- at full load
INPUT	VOLTAGE RANGE	36 ~ 72VDC
	EFFICIENCY(Typ.)	75%
	DC CURRENT(Typ.)	0.15A/48V
PROTECTION	OVERLOAD	Above 105% rated output power Protection type : Fold back current limiting, recovery automatically after fault condition is removed
	OVER VOLTAGE	5.75~ 6.75V Protection type : Hiccup mode, recovery automatically after fault condition is removed
	OVER TEMPERATURE	U1 Tj140 typically(U1)detect on main control IC Protection type : Hiccup mode, recovery automatically after temperature goes down
ENVIRONMENT	WORKING TEMP.	-10 ~ +60℃ (Refer to output load derating curve)
	WORKING HUMIDITY	20 ~ 90% RH non-condensing
	STORAGE TEMP., HUMIDITY	-20 ~ +85℃, 10 ~ 95% RH
	TEMP. COEFFICIENT	±0.05%/℃ (0 ~ 50℃)
	VIBRATION	10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes
SAFETY & EMC	WITHSTAND VOLTAGE	I/P-O/P:2KVAC
	ISOLATION RESISTANCE	I/P-O/P, I/P-FG, O/P-FG:100M Ohms / 500VDC / 25℃ / 70% RH
	EMI CONDUCTION & RADIATION	Compliance to EN55022 (CISPR22) Class B
	EMS IMMUNITY	Compliance to EN61000-4-2, 3, 4, 6, 8 ENV50204, EN55024, EN61000-6-1, light industry level, criteria A
OTHERS	DIMENSION	75*40*20mm (L*W*H)
NOTE	1. All parameters NOT specially mentioned are measured at 48VDC input, rated load and 25℃ of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. 3. Tolerance : includes set up tolerance, line regulation and load regulation. 4. The power supply is considered a component which will be installed into a final equipment. The final equipment must be re-confirmed that it still meets EMC directives.	

Mechanical Specification

Unit:mm



DC Input Connector (CN2) : MOLEX5285-03 or equivalent


Pin No.	Assignment	Mating Housing	Terminal
1	FG	MOLEX 5058 or equivalent	MOLEX 2478 or equivalent
2	(-V)		
3	(+V)		

DC Output Connector (CN1) : MOLEX5273-02 or equivalent


Pin No.	Assignment	Mating Housing	Terminal
1	+V	MOLEX 5195 or equivalent	MOLEX 5194 or equivalent
2	-V		

Block Diagram

fosc : 67KHz



Derating Curve



Static Characteristics

