

Underground Metal Detector

Model: MD-3010II



Features:

- Fully Automatic and All Metal Detectors: The MD-3010II METALS detector detects all kinds of metal objects. Unless you have set for some objects that you do not want to detect.
- LCD: The LCD comes with light, improve to identify the metal in night or caliginous out.
- Identity target: The detected objects are shown on the LCD. You can decide immediately if the objects worth to be recovered.
- Unwanted Target Elimination: You can set the detector not to respond to some objects.
- Unique Tone for Target: You do not have to keep watching the LCD display, when an object is detected, a unique tone corresponding to a target will generate. You can even look for when there is little or no light.
- Without Clumsy Slack Cable: Hidden cable reel (connection between the control unit and coil) avoid entangling and for ease of stem length adjustment.
- Earphone Jack: Provided for headphone connection. Either stereo or mono headphone can be used.
- Volume Control: To adjust the output volume for the speaker or headset.
- Battery Condition Indicator: Shows the conditions of the batteries in the battery compartment.
- Waterproof Search Coil: Lets you use the detector in the shallow water.
- Adjustable stem: allows you to adjust the length of the detector for comfortable use. The micro-plug that connects the spool and the drive controller is made of metal which makes the plug more reliable.
- Armrest & Stem: Designed to eliminate strain on forearm. Nylon bracket to further secure hand compartment slip after a long time holding the detector by arm.
- Power: Use six AA alkaline batteries 1.5 volts.

Specification:

- Battery: 6x1.5 V AA alkaline batteries (note: the battery is not allowed to send by air mail, so the batteries are not included in the box sent to you)
- Operating Current: 65mA expected, Max 150mA range
- Operating Voltage: 72-9.6 V
- Operating Frequency: 7.5 KHz +/- 1 KHz very sensitive: Min. 8 inch (Test coin: US 50 cents)
- Audio Frequency: -294 Hz (re)
 - 330 HZ (me)
 - 349 HZ (fa)
 - 392 HZ (so)
 - 440 HZ (la)
 - 494 HZ (t)
 - 523 HZ (do)
- Temperature Range: -20-60 degrees Celsius
- Size: 94cm
- Weight: 1.6 kg

Made in China